



POMPE A MOTORE
Versione a membrana

MOTOR DRIVEN PUMPS
Diaphragm version

دوزینگ پمپهای دیافراگمی

CARATTERISTICHE TECNICHE/TECHNICAL FEATURES

AMDI PVC

CODICE CODE	PORTATA FLOW-RATE	PRESSIONE PRESSURE	ml COLPO ml STROKE	TESTA DIAFRAMMA DIAPHRAGM HEAD			SPM	CORSA STROKE	MOTORE POWER	IN-OUT	PESO WEIGHT
				TESTA/HEAD	PISTONE/ PLUNGER	Ø					
AD1010506M300000	115	0	27,4	PVC	NBR/PTFE	75	70	10	0,25	FG 1/2"	15
	190	3	26,2								
	105	6	25,0								
AD1019006M300000	210	0	28,0	PVC	NBR/PTFE	75	125	10	0,25	FG 1/2"	15
	200	3	26,7								
	190	6	25,3								
AD1019006M300000	245	0	58,3	PVC	NBR/PTFE	100	70	10	0,37	FG 3/4"	16
	210	3	50,0								
	180	6	42,9								
AD1034006M300000	430	0	57,3	PVC	NBR/PTFE	100	125	10	0,37	FG 3/4"	16
	375	3	50,0								
	340	6	45,3								

AMDI AISI

CODICE CODE	PORTATA FLOW-RATE	PRESSIONE PRESSURE	ml COLPO ml STROKE	TESTA DIAFRAMMA DIAPHRAGM HEAD			SPM	CORSA STROKE	MOTORE POWER	IN-OUT	PESO WEIGHT
				TESTA/HEAD	PISTONE/ PLUNGER	Ø					
AD1010506M100000	115	0	27,4	AISI 316	NBR/PTFE	75	70	10	0,25	MG 1/2"	16
	190	3	26,2								
	105	6	25,0								
AD1019006M100000	210	0	28,0	AISI 316	NBR/PTFE	75	125	10	0,25	MG 1/2"	16
	200	3	26,7								
	190	6	25,3								
AD1019006M100000	245	0	58,3	AISI 316	NBR/PTFE	100	70	10	0,37	FG 3/4"	18
	210	3	50,0								
	180	6	42,9								
AD1034006M100000	430	0	57,3	AISI 316	NBR/PTFE	100	125	10	0,37	FG 3/4"	18
	375	3	50,0								
	340	6	45,3								

DIMENSIONI/DIMENSIONS

