



CR 3

قطر دهانه mm خروجی	قطر دهانه mm ورودی	حداکثر دبی (متر مکعب در ساعت)	حداقل هد (متر)	حداکثر هد (متر)	شدت جریان	توان موتور P _۲ HP	توان موتور P _۲ KW	RPM	ولتاژ و فاز	مدل	ردیف
1"/1¼"	1"/1¼"	1.2 - 4.43	12/18	33	1	0/5	0/37	2880	3×380-415Y	CR 3-5	1
1"/1¼"	1"/1¼"	1.2 - 4.46	23	60	1/9	1	0/75	2870	3×380-415Y	CR 3-9	2
1"/1¼"	1"/1¼"	1.2 - 4.5	28/33	73/17	2/5	1/5	1/1	2870	3×380-415Y	CR 3-11	3
1"/1¼"	1"/1¼"	1.2 - 4.47	30	80	2/5	1/5	1/1	2870	3×380-415Y	CR 3-12	4
1"/1¼"	1"/1¼"	1.2- 4.46	33/14	86/28	2/5	1/5	1/1	2870	3×380-415Y	CR 3-13	5
1"/1¼"	1"/1¼"	1.2- 4.44	37/18	99	2/5	1/5	1/1	2870	3×380-415Y	CR 3-15	6
1"/1¼"	1"/1¼"	1.2-4.52	44/23	113/7	3/15	2	1/5	2970	3×380-415Y	CR 3-17	7
1"/1¼"	1"/1¼"	1.2-4.51	44/33	126/7	3/15	2	1/5	2910	3×380-415Y	CR 3-19	8
1"/1¼"	1"/1¼"	1.2-4.54	55/95	140	4/45	3	2/2	2910	3×380-415Y	CR 3-21	9
1"/1¼"	1"/1¼"	1.2-4.53	60	154	4/45	3	2.2	2910	3×380-415Y	CR 3-23	10
1"/1¼"	1"/1¼"	1.2-4.51	67/08	167/1	4/45	3	2/2	2910	3×380-415Y	CR 3-25	11
1"/1¼"	1"/1¼"	1.2-4.52	70/94	180	4/45	3	2/2	2910	3×380-415Y	CR 3-27	12
1"/1¼"	1"/1¼"	1.2-4.53	75/35	193	4/45	3	2/2	2910	3×380-415Y	CR 3-29	13

• ۲۱-۸۸۸۳۰۰۳۱

• ۲۱-۸۸۸۳۰۰۳۲



CR 5

GRUNDFOS 

قطر دهانه خروجی mm	قطر دهانه ورودی mm	حداکثر دبی (متر مکعب در ساعت)	حداقل هد (متر)	حداکثر هد (متر)	شدت جریان	توان موتور P _r HP	توان موتور P _r KW	RPM	ولتاژ و فاز	مدل	ردیف
1"/1¼"	1"/1¼"	2.5-8.38	14/44	34/7	1/9	1	0/75	2870	3×380-415Y	CR 5-5	1
1"/1¼"	1"/1¼"	2.5-8.43	20/99	48/76	2/5	1/5	1/1	2870	3×380-415Y	CR 5-7	2
1"/1¼"	1"/1¼"	2.5-8.35	23/54	55/43	2/5	1/5	1/1	2870	3×380-415Y	CR 5-8	3
1"/1¼"	1"/1¼"	2.5-8.55	27/37	63	3/15	2	1/5	2910	3×380-415Y	CR 5-9	4
1"/1¼"	1"/1¼"	2.5-8.53	30	70	3/15	2	1/5	2910	3×380-415Y	CR 5-10	5
1"/1¼"	1"/1¼"	2.5-8.58	34/25	77/17	4/45	3	2/2	2910	3×380-415Y	CR 5-11	6
1"/1¼"	1"/1¼"	2.5-8.56	37/67	83/91	4/45	3	2/2	2910	3×380-415Y	CR 5-12	7
1"/1¼"	1"/1¼"	2.5-8.57	40	90/88	4/45	3	2/2	2910	3×380-415Y	CR 5-13	8
1"/1¼"	1"/1¼"	2.5-8.49	44/68	97/64	4/45	3	2/2	2910	3×380-415Y	CR 5-14	9
1"/1¼"	1"/1¼"	2.5-8.47	47/95	104/4	4/45	3	2/2	2910	3×380-415Y	CR 5-15	10
1"/1¼"	1"/1¼"	2.5-8.52	50	111/4	4/45	3	2/2	2910	3×380-415Y	CR 5-16	11
1"/1¼"	1"/1¼"	2.5-8.54	57/91	125/8	6/3	4	3	2920	3×380-415D	CR 5-18	12
1"/1¼"	1"/1¼"	2.5-8.49	64/63	140	6/3	4	3	2920	3×380-415D	CR 5-20	13
1"/1¼"	1"/1¼"	2.5-8.61	71/88	154/4	7/9	5/5	4	2940	3×380-415D	CR 5-22	14
1"/1¼"	1"/1¼"	2.5-8.61	80	168/1	7/9	5/5	4	2940	3×380-415D	CR 5-24	15
1"/1¼"	1"/1¼"	2.5-8.56	85/46	182/3	7/9	5/5	4	2940	3×380-415D	CR 5-26	16
1"/1¼"	1"/1¼"	2.5-8.56	94/63	203	7/9	5/5	4	2940	3×380-415D	CR 5-29	17
1"/1¼"	1"/1¼"	2.5-8.53	106/8	224/7	11	7/5	5/5	2940	3×380-415D	CR 5-32	18

• ۲۱-۸۸۸۳۰۰۳۱

• ۲۱-۸۸۸۳۰۰۳۲



CR 10

GRUNDFOS

ردیف	مدل	ولتاژ و فاز	RPM	توان موتور P _۲ HP	توان موتور P _۲ KW	شدت جریان	حداکثر هد (متر)	حداقل هد (متر)	حداکثر دبی (متر مکعب در ساعت)	قطر دهانه ورودی mm	قطر دهانه خروجی mm
1	CR 10-4	3×380-415Y	2910	2	1/5	3/15	40/91	22/32	5-13.1	1½"	1½"
2	CR 10-5	3×380-415Y	2910	3	2/2	4/45	51/36	28/83	5-13.1	1½"	1½"
3	CR 10-6	3×380-415Y	2910	3	2/2	4/45	61/52	34/83	5-13.1	1½"	1½"
4	CR 10-7	3×380-415D	2920	4	3	6/3	71/92	40	5-13.1	1½"	1½"
5	CR 10-8	3×380-415D	2920	4	3	6/3	81/99	46/44	5-13.1	1½"	1½"
6	CR 10-9	3×380-415D	2920	4	3	6/3	92	52/09	5-13.1	1½"	1½"
7	CR 10-10	3×380-415D	2940	5/5	4	7/9	102/8	59/76	5-13.1	1½"	1½"
8	CR 10-12	3×380-415D	2940	5/5	4	7/9	123/3	70	5-13.1	1½"	1½"
9	CR 10-14	3×380-415D	2940	7/5	5/5	11	144	83/21	5-13.1	1½"	1½"
10	CR 10-16	3×380-415D	2940	7/5	5/5	11	164/3	93/77	5-13.1	1½"	1½"
11	CR 10-18	3×380-415D	2920	7/5	10	14.4-14	185/5	106/2	5-13.1	1½"	1½"
12	CR 10-20	3×380-415D	2920	7/5	10	14.4-14	206	120	5-13.1	1½"	1½"
13	CR 10-22	3×380-415D	2920	7/5	10	14.4-14	226/4	129/6	5-13.1	1½"	1½"

۰۲۱-۸۸۸۳۰۰۳۱

۰۲۱-۸۸۸۳۰۰۳۲



CR 15

GRUNDFOS 

ردیف	مدل	ولتاژ و فاز	RPM	توان موتور P _۲ HP	توان موتور P _۲ KW	شدت جریان	حداکثر هد (متر)	حداقل هد (متر)	حداکثر دبی (متر مکعب در ساعت)	قطر دهانه ورودی mm	قطر دهانه خروجی mm
1	CR 15-3	3×380-415D	2920	4	3	6/3	42/7	23/19	8.62-23.7	2"	2"
2	CR 15-4	3×380-415D	2940	5/5	4	7/9	56/89	31/11	8.65-23.9	2"	2"
3	CR 15-5	3×380-415D	2940	5/5	4	7/9	70/83	38/83	8.73-23.5	2"	2"
4	CR 15-6	3×380-415D	2940	7/5	5/5	11	85	46/82	8.7-23.6	2"	2"
5	CR 15-7	3×380-415D	2940	7/5	5/5	11	99/06	55/1	8.69-23.6	2"	2"
6	CR 15-8	3×380-415D	2920	10	7/5	14.4-14	113/6	63/24	8.68-23.6	2"	2"
7	CR 15-9	3×380-415D	2920	10	7/5	14.4-14	127/6	70	8.66-23.7	2"	2"
8	CR 15-10	3×380-415D	2950	15	11	20.8-19.8	142/4	80	8.79-24	2"	2"
9	CR 15-12	3×380-415D	2950	15	11	20.8-19.8	170	96	8.7-24	2"	2"
10	CR 15-14	3×380-415D	2950	15	11	20.8-19.8	198	111/2	8.7-24	2"	2"
11	CR 15-17	3×380-415D	2950	20	15	28-26	240	134/8	8.7-24	2"	2"

• ۲۱-۸۸۸۳۰۰۳۱

• ۲۱-۸۸۸۳۰۰۳۲



CR 20

GRUNDFOS 

ردیف	مدل	ولتاژ و فاز	RPM	توان موتور P _۲ HP	توان موتور P _۲ KW	شدت جریان	حداکثر هد (متر)	حداقل هد (متر)	حداکثر دبی (متر مکعب در ساعت)	قطر دهانه ورودی mm	قطر دهانه خروجی mm
1	CR 20-4	3×380-415D	2940	7/5	5/5	11	58/8	28/89	10.7-29.4	2"	2"
2	CR 20-5	3×380-415D	2940	7/5	5/5	11	73/35	35	10.7-29.4	2"	2"
3	CR 20-6	3×380-415D	2920	10	7/5	14.4-14	88/94	45	10.7-29.4	2"	2"
4	CR 20-7	3×380-415D	2920	10	7/5	14.4-14	104	52/47	10.7-29.4	2"	2"
5	CR 20-8	3×380-415D	2950	15	11	20.8-19.8	120	60	10.8-29.4	2"	2"
6	CR 20-10	3×380-415D	2950	15	11	20.8-19.8	148/9	78/22	10.8-29.4	2"	2"
7	CR 20-12	3×380-415D	2950	20	15	28-26	178/7	92	10.8-29.4	2"	2"
8	CR 20-14	3×380-415D	2950	20	15	28-26	208	107/6	10.8-29.4	2"	2"
9	CR 20-17	3×380-415D	2950	25	18/5	34.5-32.5	251/6	130/8	10.8-29.4	2"	2"

۰۲۱-۸۸۸۳۰۰۳۱

۰۲۱-۸۸۸۳۰۰۳۲



CR 32

GRUNDFOS 

قطر دهانه خروجی mm	قطر دهانه ورودی mm	حداکثر دبی (متر مکعب در ساعت)	حداقل هد (متر)	حداکثر هد (متر)	شدت جریان	توان موتور P _۲ HP	توان موتور P _۲ KW	RPM	ولتاژ و فاز	مدل	ردیف
2½ "	2½ "	15.3-40.5	18/28	39/6	7/9	5/5	4	2940	3×380-415D	CR 32-2	1
2½ "	2½ "	15.3-40.5	30	59/16	11	7/5	5/5	2940	3×380-415D	CR 32-3	2
2½ "	2½ "	15.3-40.5	40	78/6	14.4-14	10	7/5	2920	3×380-415D	CR 32-4	3
2½ "	2½ "	15.3-40.5	50	100	20.8-19.8	15	11	2950	3×380-415D	CR 32-5	4
2½ "	2½ "	15.3-40.5	62/8	118	20.8-19.8	15	11	2950	3×380-415D	CR 32-6	5
2½ "	2½ "	15.3-40.5	70/9	138/2	28-26	20	15	2950	3×380-415D	CR 32-7	6
2½ "	2½ "	15.3-40.5	80	158/3	28-26	20	15	2950	3×380-415D	CR 32-8	7
2½ "	2½ "	15.3-40.5	104/6	196/6	34.5-32.5	25	18/5	2950	3×380-415D	CR 32-10	8
2½ "	2½ "	15.3-40.5	115/9	217	39/5	30	22	2950	3×380-415D	CR 32-11	9
2½ "	2½ "	15.3-40.5	127/2	235/7	39/5	30	22	2950	3×380-415D	CR 32-12	10

• ۲۱-۸۸۸۳۰۰۳۱

• ۲۱-۸۸۸۳۰۰۳۲



CR 1

قطر دهانه mm خروجی	قطر دهانه mm ورودی	حداکثر دبی (متر مکعب در ساعت)	حداقل هد (متر)	حداکثر هد (متر)	شدت جریان	توان موتور Pr HP	توان موتور Pr KW	RPM	ولتاژ و فاز	مدل	ردیف
1"/1¼"	1"/1¼"	0.7 - 2.36	50	92/38	1/95	1	0/75	2870	3×380-415Y	CR 1-15	1
1"/1¼"	1"/1¼"	0.7 - 2.39	52/86	105/4	2/5	1/5	1/1	2870	3×380-415Y	CR 1-17	2
1"/1¼"	1"/1¼"	0.7 - 2.39	55	117	2/5	1/5	1/1	2870	3×380-415Y	CR 1-19	3
1"/1¼"	1"/1¼"	0.7 - 2.39	62/22	129	2/5	1/5	1/1	2870	3×380-415Y	CR 1-21	4
1"/1¼"	1"/1¼"	0.7 - 2.36	80	142/7	2/5	1/5	1/1	2870	3×380-415Y	CR 1-23	5
1"/1¼"	1"/1¼"	0.7 - 2.41	80	155	3/15	2	1/5	2910	3×380-415Y	CR 1-25	6
1"/1¼"	1"/1¼"	0.7 - 2.4	86/96	167	3/15	2	1/5	2910	3×380-415Y	CR 1-27	7

• ۲۱-۸۸۸۳۰۰۳۱

• ۲۱-۸۸۸۳۰۰۳۲