

لیست قیمت پمپهای طبقاتی عمومی و نیمه صنعتی ایتالیایی DAB

| مدل | ولتاژ (v) | قدرت | | آمپر (A) | حداکثر ارتفاع (m) | ارتفاع (m) | آبدهی (m ³ /h) | | قیمت (ریال) | |
|------------|-----------|------|------|----------|-------------------|--------------------|--|--|---|--|
| | | (kw) | (hp) | | | | m ³ / h | | | |
| | | | | | | | lit / min | | | |
| KVC 35/30 | 220 | 0.45 | 0.6 | 4.1 | 40.2 | 37.3-29.8-13.5 | $\frac{1.2 - 2.4 - 3.9}{20 - 40 - 65}$ | | | |
| | 380 | | | 1.6 | | | | | | |
| KVC 45/30 | 220 | 0.75 | 1 | 5.2 | 49.7 | 46.5-38.4-19.6 | | | | |
| | 380 | 0.55 | 0.75 | 1.7 | 47.1 | 43.5-34.7-14.7 | | | | |
| KVC 50/30 | 220 | 0.75 | 1 | 6 | 61.5 | 56.8-46-22.7 | | | | |
| | 380 | | | 2.2 | | | | | | |
| KVC 60/30 | 220 | 1 | 1.36 | 6.7 | 69.6 | 64-51.1-23.8 | | | | |
| | 380 | 0.8 | 1.1 | 2.3 | | | | | | |
| KVC 65/30 | 220 | 1 | 1.36 | 7.3 | 78.4 | 73.5-61.2-33.3 | | | | |
| | 380 | | | 2.6 | | | | | | |
| KVC 70/30 | 220 | 1 | 1.36 | 6.5 | 95 | 81.5-58.7-32.5 | | | $\frac{1.2 - 2.4 - 3.3}{20 - 40 - 55}$ | |
| KVC 30/50 | 220 | 0.55 | 0.75 | 4 | 41.1 | 39-31.6-17.1 | | | $\frac{1.2 - 3 - 4.8}{20 - 50 - 80}$ | |
| | 380 | | | 1.4 | | | | | | |
| KVC 40/50 | 220 | 0.8 | 1.1 | 5.6 | 54.9 | 52-42.1-22.9 | | | | |
| | 380 | | | 2.2 | | | | | | |
| KVC 55/50 | 220 | 1 | 1.36 | 6.4 | 68.6 | 65-52.7-28.6 | | | | |
| | 380 | | | 2.6 | | | | | | |
| KVC 65/50 | 220 | 1.1 | 1.5 | 7.4 | 82.3 | 78-63.2-34.3 | | | | |
| | 380 | | | 4 | | | | | | |
| KVC 75/50 | 220 | 1.5 | 2 | 9 | 96 | 91-73.8-40 | | | | |
| | 380 | | | 4.3 | | | | | | |
| KVC 30/80 | 220 | 1 | 1.36 | 6.5 | 36.9 | 36.1-29.5-10.7 | $\frac{1.8 - 4.8 - 9}{30 - 80 - 150}$ | | | |
| | 380 | | | 2.3 | | | | | | |
| KVC 40/80 | 220 | 1.1 | 1.5 | 7.4 | 50.1 | 48-38.5-12.5 | | | | |
| | 380 | 1 | | 2.7 | | | | | | |
| KVC 45/80 | 220 | 1.6 | 2.2 | 9.7 | 64.6 | 63-52.5-21.1 | | | | |
| | 380 | | | 3.6 | | | | | | |
| KVC 55/80 | 220 | 1.85 | 2.5 | 11.2 | 76.1 | 73.9-60.5-22.7 | | | | |
| | 380 | | | 4.1 | | | | | | |
| KVC 65/80 | 380 | 2.2 | 3 | 4.8 | 88.6 | 85.5-71-30.5 | | | | |
| KVC 25/120 | 220 | 1 | 1.36 | 6.5 | 30.4 | 29.6-25.9-18.2-7 | | | $\frac{3 - 6 - 9 - 12}{50 - 100 - 150 - 200}$ | |
| | 380 | | | 2.9 | | | | | | |
| KVC 35/120 | 220 | 1.1 | 1.5 | 7.4 | 46.2 | 44-37.4-26.8-11 | | | | |
| | 380 | | | 3.5 | | | | | | |
| KVC 45/120 | 220 | 1.85 | 2.5 | 12 | 62.4 | 59.1-51.4-37.5-17 | | | | |
| KVC 60/120 | 380 | 2.2 | 3 | 5.4 | 78 | 73.9-63.2-47-24.5 | | | | |
| KVC 70/120 | | 3 | 4 | 6.8 | 95 | 89.8-77.9-59.2-31 | | | | |
| KVC 85/120 | | 3 | 4 | 7.8 | 112.7 | 105.7-89.9-66.7-34 | | | | |

KVC

دیفیوزر پروانه تکنوپلیمر
 شفت استیل 304
 قابل استفاده در دمای
 0 °C تا + 40 °C

