

لیست قیمت پمپهای سانتریفیوژ ایتالیایی (با شفت یکپارچه) CM

مدل	ولتاژ (V)	KW	HP	آمپر (A)	حداکثر ارتفاع (m)	ارتفاع (m)	دبی (m ³ /h)	ورودی (mm)	خروجی (mm)	قیمت (ریال)
CM 40-440T	380	0.7	1	1.2	4.4	4.3-3.5	2.4-6	40	40	
CM 40-540T	380	0.7	1	1.2	5.4	5.3-4.5	2.4-6	40	40	
CM 40-670T	380	0.7	1	1.3	6.7	6.6-5.8	3-6	40	40	
CM 40-870T	380	0.7	1	1.3	8.7	8.6-7.9	2.4-6	40	40	
CM 40-1300T	380	0.8	1	2	13.5	13-6	3-18	40	40	
CM 40-1450T	380	0.9	1.3	2.4	15	14.4-8	4.8-18	40	40	
CM 50-510T	380	0.7	1	1.2	5.5	5-4.2	3.6-6	50	50	
CM 50-630T	380	0.7	1	1.3	6.5	6.2-5.5	3.6-6	50	50	
CM 50-780T	380	0.7	1	1.3	8	7.7-7.1	3.6-6	50	50	
CM 50-1000T	380	0.7	1	1.4	10.5	10.1-6.8	3.6-12	50	50	
CM 50-1270T	380	1.1	1.5	2.6	13	12.7-8.5	6-18	50	50	
CM 50-1420T	380	1.1	1.5	2.6	14.5	14.2-6	6-24	50	50	
CM 65-420	380	0.25	0.33	0.8	4.2	4.1-2.1	6-24	65	65	
CM 65-540	380	0.37	0.5	1.07	5.4	5.3-3.5	6-24	65	65	
CM 65-660	380	0.55	0.75	1.4	6.6	6.5-4.8	6-24	65	65	
CM 65-760	380	0.55	0.75	1.5	7.6	6.7-5.5	18-24	65	65	
CM 65-920	380	0.75	1	2.05	9.2	9-5.7	12-30	65	65	
CM 65-1080	380	1.1	1.5	3	10.8	10.6-7.3	18-42	65	65	
CM 65-1200	380	1.5	2	3.7	12	11.9-8.9	18-42	65	65	
CM 65-1530	380	2.2	3	5.04	15.3	15.2-10.8	18-48	65	65	
CM 65-1680	380	3	4	6	16.8	16.5-12.4	18-48	65	65	
CM 65-2380	380	4	5.5	10	23.8	23.4-19	24-48	65	65	
CM 80-550	380	0.55	0.75	1.5	5.5	5.2-2.6	12-48	80	80	
CM 80-650	380	0.75	1	2	6.5	6.3-3.9	12-48	80	80	
CM 80-740	380	1.1	1.5	3	7.4	7.3-4.4	18-60	80	80	
CM 80-890	380	1.5	2	3.7	8.9	8.8-6.6	18-60	80	80	
CM 80-1050	380	2.2	3	5.04	10.5	10.4-8.8	24-60	80	80	
CM 80-1530	380	3	4	6	15.3	15-11.3	36-72	80	80	
CM 80-1700	380	4	5.5	10	17	16.8-12.6	42-84	80	80	
CM 80-2410	380	5.5	7.5	12.7	24.1	23.8-18.6	24-72	80	80	
CM 80-2700	380	7.5	10	16	27	26-19	42-90	80	80	
CM 80-3420	380	11	15	24	34.2	33.2-21.7	42-114	80	80	
CM 100-510	380	0.75	1	2	5.1	4.9-3	12-60	100	100	

لیست قیمت پمپهای سانتریفیوژ ایتالیایی (با شفت یکپارچه) CM

مدل	ولتاژ (V)	KW	HP	آمپر (A)	حداکثر ارتفاع (m)	ارتفاع (m)	نسبی (m ³ /h)	ورودی (mm)	خروجی (mm)	قیمت (ریال)
CM 100-650	380	1.1	1.5	3	6.5	6.4-4.6	12-60	100	100	
CM 100-660	380	1.5	2	3.7	6.6	6.4-3	30-114	100	100	
CM 100-865	380	2.2	3	5.04	8.6	8.5-4.6	30-120	100	100	
CM 100-1020	380	3	4	6	10.2	10.1-6.7	36-120	100	100	
CM 100-1320	380	4	5.5	10	13.2	12.9-8.7	60-120	100	100	
CM 100-1650	380	5.5	7.5	12.7	16.5	16.2-12.7	60-120	100	100	
CM 100-2050	380	7.5	10	16	20.5	20-16	72-120	100	100	
CM 100-2550	380	11	15	24	25.5	25.1-21	60-120	100	100	
CM 100-3290	380	15	20	31	32.9	32.8-24	72-150	100	100	
CM 100-3680	380	18.5	25	38	36.8	36.5-29.5	84-150	100	100	
CM 100-4100	380	22	30	44	41	40.6-29	84-180	100	100	
CM 125-1075	380	4	5.5	10	10.8	10.1-5.4	60-180	125	125	
CM 125-1270	380	5.5	7.5	12.7	12.7	12.6-8.5	60-180	125	125	
CM 125-1560	380	7.5	10	16	15.6	15.4-9.8	60-120	125	125	
CM 125-2100	380	11	15	24	21	20.9-16	102-180	125	125	
CM 125-2550	380	15	20	31	25.5	25.1-17.5	84-210	125	125	
CM 125-3200	380	18.5	25	38	32	31.5-23	84-180	125	125	
CM 125-3600	380	22	30	44	36	35.5-24	84-210	125	125	
CM 125-4022	380	30	40	58	40.2	39.7-26.8	84-210	125	125	
CM 150-955	380	5.5	7.5	12.7	9.6	9.4-5.6	210-300	150	150	
CM 150-1322	380	7.5	10	16	13.2	13-8.5	90-250	150	150	
CM 150-1600	380	11	15	24	16	15.5-9.2	102-300	150	150	
CM 150-1950	380	15	20	31	19.5	19.4-10.9	114-360	150	150	
CM 150-2200	380	18.5	25	38	22	21.9-12	114-390	150	150	
CM 150-2405	380	22	30	44	24.1	23.9-14	102-420	150	150	



DAB
PUMP PERFORMANCE

خصوصیات پمپهای سانتریفیوژ (با شفت یکپارچه) CM :

۱- مصارف آبرسانی سیرکولاتور آب سرد (۱۰°C-) و آب گرم (۱۴°C+)

۲- استفاده در برجهای خنک کننده و گردش آب .

۳- برای مصارف کشاورزی - باغبانی و صنعتی و پروژه های پمپاژ آب.