



# Hot water high-pressure cleaner

## LKX XP (three phase)

Accessory holder  
Power cable holder



BX4 15-200

Ergonomic handle

Panel with analogic controls

Heavy frame



### Standard equipment:

- Gun with rotating coupling.
- Lance with nozzle-holder.
- Power cable 5 m
- High pressure hose 10 m



- Vertical burner with high thermal efficiency steel coil.
- Temperature regulation gauge.
- Safety valve.
- Low fuel lamp.



- Auxiliary motor for burner.

### Optional:

- Hose-reel with brake (hose not included) cod. 3.697.0044
- On request models with header tank and/or antiscaling device.
- Antiscaling LC-PRECAL (pcs. 4 x 5 lt.) cod. 3.697.0044



|                              | LKX 1515 XP               | LKX 2015 XP                |
|------------------------------|---------------------------|----------------------------|
| Code                         | 8.621.0902                | 8.621.0903                 |
| operat. pressure/max         | 30÷150 bar                | 30÷200 bar                 |
| operat. pressure/max         | 435÷2175 psi              | 435÷2900 psi               |
| delivery rate                | 450÷900 l/h               | 450÷900 l/h                |
| delivery rate                | 1.98÷3.96 GPM             | 1.98÷3.96 GPM              |
| abs. power/voltage           | 5500W - 400V~50Hz         | 7300W - 400V~50Hz          |
| RPM                          | 1450 RPM                  | 1450 RPM                   |
| diesel tank/detergent tank   | 18/3,0 l.-4.8/0.79 gal    | 18/3,0 l.-4.8/0.79 gal     |
| max temp. inlet/outlet       | 40 °C / 140 °C            | 40 °C / 140 °C             |
| fuel consumption/heat output | 5,6 l/h-1.5 gal/h / 74 kW | 5,6 l/h- 1.5 gal/h / 74 kW |
| machine dimensions           | 94x65x90 cm               | 94x65x90 cm                |
| machine weight               | 114 Kg / 250.8 lbs        | 116 Kg / 255.2 lbs         |

