

## ۱- جدول ظرفیت مبدل های حرارتی هیپاکو (آب به آب)

ردیف	مدل	دبی آب مصرفی ( $\Delta t=50^{\circ}\text{C}$ ) (lit/Hr)	سایز ورودی و خروجی طرف سرد S (inch)	سایز ورودی و خروجی طرف داغ B (inch)	طول H(mm)	عرض W(mm)	عمق D(mm)	وزن (kg)	توان حرارتی (kcal/hr)
1	HP - 40	400	1/2	3/4	193	84	45.8	1.20	20,000
2	HP - 50	500	3/4	3/4	193	84	50.4	1.30	25,000
3	HP - 60	600	3/4	3/4	193	84	55.0	1.40	30,000
4	HP - 80	800	3/4	3/4	193	84	68.8	1.70	40,000
5	HP - 100	1,000	3/4	3/4	193	84	91.8	2.20	50,000
6	HP - 120	1,200	3/4	3/4	193	84	101.0	2.40	60,000
7	HP - 150	1,500	3/4	3/4	193	84	105.6	2.50	75,000
8	HP - 200	2,000	1	1 1/4	311	111	64.2	3.60	100,000
9	HP - 250	2,500	1	1 1/4	311	111	73.4	4.00	125,000
10	HP - 300	3,000	1	1 1/4	311	111	87.2	4.60	150,000
11	HP - 350	3,500	1	1 1/4	311	111	101.0	5.20	175,000
12	HP - 400	4,000	1	1 1/4	311	111	114.8	5.80	200,000
13	HP - 500	5,000	1 1/4	1 1/4	527	120	91.8	9.42	250,000
14	HP - 600	6,000	1 1/4	1 1/4	527	120	110.2	10.98	300,000
15	HP - 750	7,500	2	2	530	250	68.2	16.60	375,000
16	HP - 900	9,000	2	2	530	250	82.0	19.00	475,000
17	HP - 1200	12,000	2	2	530	250	105.0	23.00	600,000
18	HP - 1500	15,000	2	2	530	250	128.0	27.00	750,000
19	HP - 1800	18,000	2	2	530	250	174.0	35.00	900,000

