

NPX XP



Standard equipment:

- Gun with rotating coupling.
- Lance with nozzle-holder.
- Power cable 5 m
- High pressure hose 10 m



- Vertical burner with high thermal efficiency steel coil.
- Temperature regulation gauge.
- Safety valve.
- Low fuel lamp.



- Heavy duty steel frame.

Optional:

- Hose-reel with brake (hose not included) cod.3.697.0044



	NPX 1211 XP	NPX 1511 XP	NPX 1813 XP
Code	8.620.0601	8.620.0602	8.620.0603
operat. pressure/max	30÷120 bar (max 150 bar)	30÷150 bar	30÷180 bar
operat. pressure/max	435÷1450 psi (max 1740)	435÷2175 psi	435÷2610 psi
delivery rate	330÷660 l/h	330÷660 l/h	400÷780 l/h
delivery rate	1.71÷3.43 GPM	1.71÷3.43 GPM	1.76÷3.43 GPM
abs. power/voltage	3200W - 230V~50Hz	4000W - 400V~50Hz	6300W - 400V~50Hz
RPM	2800 RPM	2800 RPM	2800 RPM
diesel tank/detergent tank	18/3,0 l. - 4.76/0.79 gal	18/3,0 l. - 4.76/0.79 gal	18/3,0 l. - 4.76/0.79 gal
max temp. inlet/outlet	40 °C / 140 °C	40 °C / 140 °C	40 °C / 140 °C
fuel consumption/heat output	3,78 l/h - 1 gal/h / 42 kW	3,78 l/h - 1 gal/h / 42 kW	3,78 l/h - 1 gal/h / 42 kW
machine dimensions	94x65x90 cm	94x65x90 cm	94x65x90 cm
machine weight	97 kg / 213.4 lbs	98 kg / 215.6 lbs	99 Kg / 217.8 lbs