



TS
Total Stop 24V

700 mm | 400 mm

Standard equipment:

- Gun with rotating coupling.
- Lance with nozzle-holder.
- Power cable 5 m
- High pressure hose 10 m



- Low voltage main switch (24 V)



- Vertical burner with high thermal efficiency steel coil.
- Auxiliary motor for burner.



- Header tank and antiscaling device.

Optional:

- Hose-reel with brake (hose not included) cod. 6.608.0010
- Antiscale LC-PRECAL (pcs. 4 x 5 lt.) cod. 3.697.0044



	TEKNA 1515 LP	TEKNA 2015 LP
Code	8.622.0901	8.622.0902
operat. pressure/max	30÷150 bar	30÷200 bar
operat. pressure/max	435÷2175 psi	435÷2900 psi
delivery rate	450÷900 l/h	450÷900 l/h
delivery rate	1.98÷3.96 GPM	1.98÷3.96 GPM
abs. power/voltage	5500W - 400V~50Hz	7300W - 400V~50Hz
RPM	1450 RPM	1450 RPM
diesel tank/detergent tank/antiscaling	22/22/2,4 l - 5.82/5.82/0.63 gal	22/22/2,4 l - 5.82/5.82/0.63 gal
max temp. inlet/outlet	40 °C / 140 °C	40 °C / 140 °C
fuel consumption/heat output	4.72 l/h - 1.25 gal/h / 58 kW	4.72 l/h - 1.25 gal/h / 58 kW
machine dimensions	125x69x87 cm	125x69x87 cm
machine weight	138 Kg / 303.69 lbs	143 kg / 314.6 lbs